

## ELECTROBOMBA ITUR S4-100M 0.75 (Ref.CAM1831 )

### Serie S

Bombas sumergibles de reducido diámetro  
Multicelulares con la bomba bajo el motor



| TIPO DE BOMBA | P2 Potencia del motor kW / HP | Corriente Clase | Ø mm   | H Altura manométrica en metros | Caudal en m <sup>3</sup> /hora |       |       |      |      |      |      |      |      |      |      |     |     |     |     |     |
|---------------|-------------------------------|-----------------|--------|--------------------------------|--------------------------------|-------|-------|------|------|------|------|------|------|------|------|-----|-----|-----|-----|-----|
|               |                               |                 |        |                                | 0,9                            | 1,9   | 1,5   | 2,2  | 2,5  | 3,0  | 4,0  | 5,0  | 6,0  | 6,3  |      |     |     |     |     |     |
| S4-100M       | 0,75 1,00                     | Mon             | 1 1/4" | 4"                             | 12,0                           | 62,0  | 48,0  | 38,0 | 30,0 | 19,0 | 7,0  |      |      |      |      |     |     |     |     |     |
| S4H-100M      | 0,75 1,00                     | Mon             | 2 3/8" | 4"                             | 13                             | 100,0 | 78,0  | 60,0 | 42,0 | 22,0 |      |      |      |      |      |     |     |     |     |     |
| S4S-100M      | 0,75 1,00                     | Mon             | 2 3/8" | 4"                             | 14                             | 140,0 | 110,0 | 85,0 | 72,0 | 44,0 |      |      |      |      |      |     |     |     |     |     |
| SC4-100M      | 0,75 1,00                     | Mon             | 2 3/8" | 4"                             | 13                             | 21,0  | 19,0  | 17,0 | 16,0 | 15,0 | 14,0 | 13,0 | 12,0 | 11,0 | 10,0 | 9,0 | 8,0 | 7,0 | 6,0 | 5,0 |
| SC4S-100M     | 1,10 1,50                     | Mon             | 2 3/8" | 4"                             | 15                             | 100,0 | 84,0  | 66,0 | 60,0 | 75,0 | 60,0 | 49,0 | 21,0 |      |      |     |     |     |     |     |
| SS-100M       | 0,60 0,80                     | Mon             | 2 3/8" | 5"                             | 12                             | 40,0  | 35,0  | 32,0 | 29,0 | 26,0 | 24,0 | 18,0 | 8,0  | 1,0  |      |     |     |     |     |     |
| SS-100MS      | 0,60 0,80                     | Mon             | 2 3/8" | 5"                             | 12                             | 40,0  | 35,0  | 32,0 | 29,0 | 26,0 | 24,0 | 18,0 | 8,0  | 1,0  |      |     |     |     |     |     |
| SS-100M       | 0,90 1,20                     | Mon             | 2 3/8" | 5"                             | 13                             | 60,0  | 53,0  | 50,0 | 47,0 | 43,0 | 40,0 | 30,0 | 20,0 | 9,0  | 2,0  |     |     |     |     |     |
| SS-100MS      | 0,90 1,20                     | Mon             | 2 3/8" | 5"                             | 13                             | 60,0  | 53,0  | 50,0 | 47,0 | 43,0 | 40,0 | 30,0 | 20,0 | 9,0  | 2,0  |     |     |     |     |     |
| SS-100M       | 1,20 1,60                     | Mon             | 2 3/8" | 5"                             | 15                             | 80,0  | 73,0  | 69,0 | 63,0 | 60,0 | 56,0 | 45,0 | 31,0 | 13,0 | 2,0  |     |     |     |     |     |
| SS-100MS      | 1,20 1,60                     | Mon             | 2 3/8" | 5"                             | 15                             | 80,0  | 73,0  | 69,0 | 63,0 | 60,0 | 56,0 | 45,0 | 31,0 | 13,0 | 2,0  |     |     |     |     |     |

| TIPO DE BOMBA | P2 Potencia del motor kW / HP | Corriente Clase | Ø mm   | H Altura manométrica en metros | Caudal en m <sup>3</sup> /hora |      |      |      |      |      |      |      |      |      |      |     |     |     |     |     |
|---------------|-------------------------------|-----------------|--------|--------------------------------|--------------------------------|------|------|------|------|------|------|------|------|------|------|-----|-----|-----|-----|-----|
|               |                               |                 |        |                                | 1                              | 4    | 6    | 8    | 10   | 12   | 13   | 14   | 16   | 17   |      |     |     |     |     |     |
| SXS-12020M    | 1,50 2,00                     | Mon             | 2 3/8" | 5"                             | 15                             | 53,0 | 44,0 | 38,0 | 30,0 | 21,0 | 10,0 | 4,0  |      |      |      |     |     |     |     |     |
| SXS-12020T    | 1,50 2,00                     | Tif             | 4 1/2" | 5"                             | 15                             | 53,0 | 44,0 | 38,0 | 30,0 | 21,0 | 10,0 | 4,0  |      |      |      |     |     |     |     |     |
| SXS-16200M    | 1,50 2,00                     | Mon             | 2 3/8" | 5"                             | 15                             | 43,0 | 38,0 | 36,0 | 33,0 | 28,0 | 22,0 | 19,0 | 13,0 | 6,0  |      |     |     |     |     |     |
| SXS-16200T    | 1,50 2,00                     | Tif             | 4 1/2" | 5"                             | 15                             | 43,0 | 38,0 | 36,0 | 33,0 | 28,0 | 22,0 | 19,0 | 13,0 | 6,0  |      |     |     |     |     |     |
| SXS-18200M    | 2,00 2,80                     | Tif             | 4 1/2" | 5"                             | 17                             | 44,0 | 38,0 | 36,0 | 33,0 | 28,0 | 22,0 | 19,0 | 13,0 | 7,0  | 7,0  | 7,0 | 7,0 | 7,0 | 7,0 | 7,0 |
| SXS-18400T    | 3,00 4,00                     | Tif             | 4 1/2" | 5"                             | 17                             | 68,0 | 61,0 | 56,0 | 52,0 | 45,0 | 30,0 | 25,0 | 31,0 | 22,0 | 17,0 |     |     |     |     |     |

itur-S-SH-SQ-SX.jpg

ELECTROBOMBA ITUR S4-100M 0.75 (Ref.CAM1831, 990110462, S4-100M)

Calificación: Sin calificación

Precio

On Order



[Haga una pregunta sobre este producto](#)

Fabricante: [Bombas Itur](#)

Descripción

Comentarios

Aún no hay comentarios para este producto.

// //